

A SHORT COURSE ON ELECTRONIC EYELETS

Helpful information and application data from the electronic eyelet specialist since **1973**

What are electronic eyelets?

Electronic eyelets are flanged tubular metal conductors inserted into a printed circuit board. They make electrical continuity between the circuitry on both sides of the board, and are an attachment point for soldering component leads.

What is the proper length for an eyelet?

Usually a minimum of .030 should be allowed to roll the setting on small eyelets. Conditions will vary and tests with samples are advised.

What is the diameter of the rolled clinch setting?

The diameter of the rolled clinch setting is usually .030 to .040 more than the barrel's outside diameter (O.D.)

Why are eyelets made from both brass and copper?

Small sizes are made from copper because fabrication and setting is easier. Large sizes are made from brass for increased strength.

What kind of brass is used to make International Eyelets's electronic eyelets?

An alloy of 70% copper and 30% zinc specified as QQB-613B Comp.2

What type of copper is used for International Eyelet's electronic eyelets?

OFHC (Oxygen-Free High Conductivity) QQC-576B

Why are eyelets gold plated?

When electroplated to a thickness of 30 to 50 microns, 24K gold protects the metal from oxidizing and prolongs the shelf life of the solderable surfaces.

Why are some eyelets plated with tin?

Tin plating improves solderability, avoids the cost of gold plating, and avoids the weakening of soldered joints caused by gold diffusion.

Why are flat flange eyelets used?

Because of the smaller flange diameter, flat flange eyelets may be spaced closer together. Solder also flows easier under a flat flange than under a roll flange.

What is the purpose of the rolled flange eyelet?

The roll flange makes a 360 degree contact with the copper land on the printed circuit board, and the contact pressure is maintained by the spring pressure of the arched flange.

What is the purpose of the funnel flange eyelets?

Specifically developed for electronic use, funnel flange eyelets allow solder to flow around the barrel. Lead wires are easier to insert and the solder fillet is quickly inspected.

How can eyelets be used to rework or salvage plated holes in printed circuit boards?

Rework or salvage plated holes by just inserting any style eyelet of the proper size into the plated hole and setting it in the normal manner. If a larger size eyelet is used, drill out the plated hole to a larger size.

Why is visual inspection easier with eyelets?

Since eyeleted holes have solid metal walls, it is not necessary to look for discontinuity or voids as in plated holes.

How are eyelets added to printed circuit boards for retrofitting components or circuit modification?

COMPONENTS MAY BE ADDED TO EXISTING CIRCUIT BOARDS BY DRILLING HOLES ADJACENT TO CONDUCTORS AND INSERTING EYELETS IN CONTACT WITH THE COPPER. Eyelets can also be added for durable test-point connections. Jumper wires can be anchored to eyelets. Reliable feed-through connections between conductors on two sided boards are assured when eyelets are used.

How are eyelet setting tools used?

Setting tools consist of two parts. The anvil holds the eyelet on a retracting spindle and supports the flange and the form tool or die applies the force and curvature necessary to roll the exposed barrel until it is seated firmly against the board.

How are setting tools mounted for setting eyelets?

Setting tools should be mounted in a press which will maintain the tools in alignment and apply a steady pressure on the eyelet. Specialized presses are available or an arbor or drill press may be used.

Can eyelets be resoldered?

Unlike plated-through holes, eyelets are not damaged by soldering heat and can be resoldered several times. An eyelet's wall thickness is 30 times that of plated-through hole and the mechanical clinching of an eyelet is not affected when removing de-soldered components.

What causes a rolled setting to split?

Roll settings can split for the following reasons: the metal is too hard, the setting tools are misaligned or the setting tools are the wrong size or improperly designed. Split eyelets were previously a cause for rejection but are now accepted. Splitting is sometimes induced by tools which over stress the roll or by the use of pre-scored eyelets that facilitate solder flow.

What types of eyelet setting tools are available?

Roll setting tools are used for most electronic eyelets. It will accommodate for board thickness variations and produce a firm clinch. Funnel setting tools are not commonly used because the taper stretches and splits the metal and a tight clinch is not attainable. Copper eyelets tend to be more successful with funnel setting tools.

What causes an eyelet's barrel to deform or collapse?

- The eyelet is too long.
- The holes in the printed circuit board are too large.
- The eyelet metal is too soft.
- The setting tools are misaligned or improperly designed.

What are other uses for eyelets in electronic packaging?

- Spacers for components and mother boards.
- Standoffs for large components.
- Sleeve guides for leads.
- Grommets for leads.
- Strain relief points for leads.
- Guides for screws and pins.
- Telescoping pairs making sliding fits.
- Bearings for shafts.
- Captive washers for nuts.

IEI is the chosen eyelet supplier for the Aerospace Industry. Call the Sales Department and receive the same excellent service that we give to all customers big or small.